

# POZZOLITH<sup>®</sup> 664

(Formerly Rheobuild 864)

## High range, water-reducing superplasticiser for rheoplastic concretes

### Description of Product

POZZOLITH 664 is a specially designed superplasticiser formulated from synthetic polymers to impart rheoplastic qualities to concrete.

A rheoplastic concrete is a fluid concrete, easily flowing, but at the same time free from segregation and bleeding having the same w/c ratio as that of a low slump concrete without admixture with a slight set retarding effect. Also, it provides a substantial water reduction effect for promoting high, early and ultimate strengths.

POZZOLITH 664 is chloride-free.

### Advantages

POZZOLITH 664 considerably improves the properties of fresh and hardened concrete.

### Primary Uses

- Microsilica concrete
- Mass concrete pours
- Ready-mixed concrete
- Long distance transport
- Pumped concrete
- Casting in hot climates

### To obtain:

- Reduced thermal peaks
- High workability for longer periods
- Lower pumping pressure
- Delayed setting with longer workability
- Higher ultimate strengths
- Reduced permeability
- Improved durability

### Compatibility

POZZOLITH 664 is compatible with all cements and most air-entraining agents meeting ASTM standards. The addition of POZZOLITH 664 and MICRO AIR 111 (air-entraining agent) to concrete is recommended where it is required to withstand freezing and thawing cycles.

### Packaging

POZZOLITH 664 is available in 25ltr pails, 210ltr drums or 1000ltr bulk.

### Typical Properties

Colour:	Dark brown liquid
Specific gravity:	1.2+ 0.010 (1.190 to 1.210)
Chloride content:	Nil to BS 5075
Nitrate content:	Nil
Freezing point:	0°C
Flashpoint:	N/A

### Standards

ASTM C-494: Types D and G

BS 5075: Part 3

### Dosage

Optimum dosage of POZZOLITH 664 should be determined in trial mixes. As a guide, the following dosages are recommended as a starting point for any trial: in normal concrete, a dosage of between 0.8-2ltr/100kg of cement.

Please consult BASF's Technical Services Department for further information.

### Dispensing

POZZOLITH 664 is a ready-to-use liquid, which is dispensed into the concrete together with the mixing water. The plasticising effect and water reduction are higher if the admixture is added to the concrete after 50 to 70% of the mixing water has been added. The addition of POZZOLITH 664 to dry aggregate or cement is not recommended. Automatic dispensers are available.

### Workability

POZZOLITH 664 ensures that rheoplastic concrete remains workable in excess of 2 hours at +20°C.

Workability loss is dependent on temperature, the type of cement, nature of aggregates, method of transport and initial workability. It is strongly

***Adding Value to Concrete***



The Chemical Company

# POZZOLITH<sup>®</sup> 664

(Formerly Rheobuild 864)

recommended that concrete should be properly cured, particularly in hot and dry climates.

## Storage

POZZOLITH 664 must be stored where temperatures do not drop below +5 °C. If product has frozen, thaw and agitate until completely reconstituted. Store under cover, out of direct sunlight and protect from extremes of temperature.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice, consult BASF's Technical Services Department.

## Shelf Life

Up to 24 months if stored according to manufacturer's instructions in unopened containers.

## Note

Field service, where provided, does not constitute supervisory responsibility. For additional information, contact your local BASF representative.

BASF reserves the right to have the true cause of any difficulty determined by accepted test methods.

## Quality Statement

All products manufactured by BASF Egypt, or imported from BASF affiliate companies world-wide, are manufactured to procedures certified to conform to the quality, environment, health & safety management systems described in the ISO 9001:2000, ISO 14001:2004 & OHSAS 18001:1999 standards.

12/07 BASF-EG

BASF-CC, Egypt  
55, St. 18, Maadi Sarayat  
11431 Cairo, Egypt  
Factory: Sadat City, Piece 118  
Zone 4

Tel.: +2 012 393 98 44  
Tel.: +2 012 398 67 78  
Tel.: +2 012 390 22 35  
Tel.: +2048 2604842  
Fax: +2048 2604757

Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

e-mail: [enquire.egypt@basf.com](mailto:enquire.egypt@basf.com), website: [www.basf-cc.com.eg](http://www.basf-cc.com.eg)

As all BASF technical datasheets are updated on a regular basis, it is the user's responsibility to obtain the most recent issue. Most recent issue is available on the website at [www.basf-cc.com.eg](http://www.basf-cc.com.eg)

\* Properties listed are only for guidance and are not a guarantee of performance.

